

# **Electric Lock**

## **Electric Strike**

#### AI-130NO/NC

- · Standard, concealed installation
- Power-off to lock(NO) Power-on to lock(NC
- · Working Voltage: DC12V input
- Working Current: 240mA(NO) 120mA(NC)
- Holding Force: 250kg
- · Weight: 0.37kg
- Lock jaw size: 29×17×11mm
- Lock body size: 150×28×35mm
- Suitable for: Wooden door
- · Fail Secure/Fail Safe

## AL-131NO/NC



- Power-off to lock(NO) Power-on to lock(NC)
- Working VoltageDC12V input
- Working Current240mA(NO) 120mA(NC)
- Holding Force: 400kg
- · Weight 0.38kg
- Lock jaw size 45×17×11mm
- Lock body size 150×28×35mm
- Suitable for: Metallic door
- · Fail Secure/Fail Safe



#### AL-132NO/NC

## AL-133NC

- Special, wide-mouthed, concealed installation
- Power-off to lock(NO) Power-on to lock(NC)
- · Working Voltage: DC12V input
- Working Current: 240mA(NO) 120mA(NC)
- · Holding Force: 400kg
- · Weight: 0.41kg
- Lock jaw size: 45×17×13mm
- Lock body size: 240×25×35mm
- Suitable for: Metallic door
- Fail Secure / Fail Safe



- concealed installation Power-on to lock
- Working Voltage: DC12V input
- Working Current: 240mA(NO) 120mA(NC)
- · Holding Force: 250kg Weight: 0.37kg
- Lock jaw size: 29×13×11mm
- · Lock body size: 150×28×35mm
- Suitable for: Metallic door
- Fail Safe



## AL-100

## AL-300



- Concealed installation
- Power-on to lock, Door status signal NC output
- Working Voltage: DC12V input
- · Working Current: 350mA
- Holding Force: 1000kg
- Weight: 0.72kg
- Size: 200×35×38mm



- Concealed installation
- Power-on to lock, lock status LED display, Door status signal NC output
- Working Voltage: DC12V input
- Working Current: 350mA
- Holding Force: 1000kg
- Weight: 0.77kg
- Size: 200×35×38mm

## AL-100PF

# Approved Local Manageria of receiving particles Manageria Consumption (3)

- · Electric bolt bracket in frameless glass door
- For installation of the drop bolt
- 8 -12mm thick frameless glass doors

## AL-200PZ



- · Electric bolt bracket in frameless glass door
- For installation of lock
- 8 -12mm thick frameless glass doors

# Electromagnetic Lock

#### AL-180M



- Power-on to lock
- Holding Force: 150kg
- Working Voltage: DC12V input
- · Weight: 1.02kg
- Size: 198×21×35mm

#### AI-180



- · Power-on to lock Working
- · Voltage: DC12V input
- · Holding Force: 150kg
- · Weight: 1.07kg
- Size: 166×21×41mm

## AL-180D



- Power-on to lock Working
- · Voltage: DC12V input
- Holding Force: 2×150kg
- · Weight: 2.15kg
- Size: 332×21×41mm

## AL-280(LED)



- Power-on to lock
- · Holding Force: 270kg
- Working Voltage: DC12V/24V input
- · Weight: 1.97kg
- Size: 253×25×48mm

## AL-280D(LED)



- Power-on to lock
- · Holding Force: 2×270kg
- Working Voltage: DC12V/24V input
- Weight: 3.90kg
- Size: 506×25×48mm

## AL-350(LED)



- Power-on to lock
- Holding Force: 300kg
- Working Voltage: DC12V/24V input
- · Weight: 2.46kg
- Size: 253×28×55mm

## AL-350D(LED)



- Power-on to lock
- Holding Force: 2×300kg
- · Working Voltage: DC12V/24V input
- · Weight: 4.92kg
- Size: 506×28×55mm

# AL-500(LED)



- Power-on to lockHolding Force: 500kg
- Working Voltage: DC12V/24V input
- Weight: 4.48kg
- Size: 280×38×70mm



AL-500D(LED)

- Power-on to lock
- Holding Force: 2×500kg
- Working Voltage: DC12V/24V input
- · Weight: 8.96kg
- Size: 560×38×70mm

# **Electric Cabinet Lock**

## AL-400



- Electric lock for storage box
- Power Supply: DC 12V 0.6A
- Dimension: 54.5mm×41mm×28mm

# Brackets for electromagnetic locks

## AL-180/280/350PL



- L bracket for AL180/280(LED)/350(LED)
- To install the lock body

## AL-180/280/350DPL



- L bracket for AL180D/280D(LED)/350D(LED)
- To install the lock body

## AL-500PL



- L bracket for AL-500(LED)
- To install the lock body

## AL-500DPL



- L bracket for AL-500D(LED)
- To install the lock body

## AL-350PU



- U bracket for AL-350/350D
- To intall the iron plate on the glass door (the lock body install on the frame door)

## AL-500PZ



- Z bracket for AL-500(LED)/AL-500D(LED)
- To install the iron plate

## AL-180/280PU



- U bracket for AL180/280/180D/280D
- · To intall the iron plate on the glass door (the lock body install on the frame door)

## AL-180PZ



- Z bracket for AL-180
- · To install the iron plate

## AL-500PU



- U bracket for AL-500/500D
- To intall the iron plate on the glass door (the lock body install on the frame door)

## AL-280/350PZ



- · Z bracket for AL-280(LED)/AL-280D(LED)/ AL-350(LED)/AL-280D(LED)
- · To install the iron plate









